



RUGGED, RELIABLE, AND READY

MAHINDRA IMPLEMENTS

PRACTICAL EVERYDAY TOOLS



Mahindra

TABLE OF CONTENTS

Intro	3
Pallet Forks	4 – 5
Bale Spears	6 – 7
Rake Grapples	8 – 9
JAWZ™ Grabbing Tool	10 – 11
Grapple Add-on	12 – 13
4-in-1 Buckets	14 – 15
Rock Buckets	16 – 17
Standard-duty Rotary Cutters	18 – 19
Medium-duty Rotary Cutters	20 – 21
Heavy-duty Rotary Cutters	22 – 23
Flex Wing Rotary Cutters	24 – 27
Finish Mowers	28 – 29
Shredders	30 – 31
Box Scrapers	32 – 33
Tillers	34 – 37
Medium-duty Disc Harrows	38 – 39
Heavy-duty Disc Harrow	40 – 41
Power Harrow	42 – 43
Rear Blades	44 – 45
Landscape Rakes	46 – 47
Harley Power Rakes	48 – 49
Land Levelers	50 – 51
Augers	52 – 53
Compactors	52 – 55
Spreaders	56 – 57
Plow	58 – 59
Hitches	60 – 61
Boom Pole	62 – 63

[1] 2018 Data including all Mahindra group brand sales.



TOUGH TRACTORS. TRIED-&-TRUE TOOLS.

Mahindra is the fastest growing tractor brand in North America and the World's No. 1 selling farm tractor.^[1] We put our heart and soul into customer service, quality, and value.

Mahindra implements are a superior choice. They're engineered to be as tough as our tractors, then tested in the field to ensure they meet the strictest standards. They are value-packed with must-have features too. Your Mahindra implements will last for years of uninterrupted performance, so you can focus on transforming the property you own into the land you love!

In this guide, we've taken the time to eliminate the guesswork by matching all current-selling tractors to dozens of available implements. But if you are a novice, no worries! There are 500 Mahindra dealers ready to guide you toward the right tool.



Mahindra



PALLET FORKS

TRANSPORT ALMOST EVERYTHING

Mahindra heavy-duty pallet forks are back savers. They are ideal when transporting bulky and weighty materials like logs, stumps, fence posts, lumber, firewood, crates, totes, and heavy equipment. Our customers have used Mahindra pallet forks for unique applications as well. Some use them to place their 4-wheelers and riding mowers into their pickup trucks. Others transport round bales and convert them into a cherry picker. One customer even uses them as an engine hoist.

FEATURES & BENEFITS

- Reduce downtime using its quick skid steer connect
- Safely and easily adjust fork spacing to match load width
- Protect the tractor and operator from materials via vertical guards
- Designed to economically and quickly replace damaged forks
- Available in two sizes to accommodate any size Mahindra tractor
- One-year warranty for peace of mind



SPECIFICATIONS

FORK FEATURES	PALLET FORKS 2000	PALLET FORKS 4000
Connector Type	Skid Steer	
Maximum Lift Capacity (lb)	2000	4000
Overall Height (in)	30	34
Overall Length (in)	46.5	
Vertical Guard Bars	8	5
Fork Replacement	Yes	
Fork size (in)	3 wide x 1 thick	4 wide x 1.25 thick
Fork Length (in)	42	48
Rails	Locking Slide	
Min/Max Adjustable Widths (in)	1.5 to 44.5	4 to 45.0
Weight (lb)	236	400
Warranty	1-Year Limited	
SKU No.	AMIAPF200	AMIAPF400
TRACTOR COMPATIBILITY	PALLET FORKS 2000	PALLET FORKS 4000
Max 25XL	X	
Max 26XLT	X	
1626	X	
1635	X	
1640	X	
2638	X	
2645	X	
2660		X
2670		X
3640		X
3650		X
4540 2WD / 4WD		X
4550 4WD		X
6065 / 6075		X
7085 / 7095		X
8090 / 8100		X
9110 / 9125		X



BALE SPEARS

FETCH ROUND BALES OF HAY AND SILAGE

Ideal for medium to large livestock and mixed farms, our heavy-duty bale spears are engineered for handling 500- to 2000-lb round hay and silage bales. They come in two configurations. A single spear is excellent for small round bales while the double spear tackles large round or square bales. Some customers utilize the double spears as pallet forks too.

FEATURES & BENEFITS

- Reduce downtime using its quick skid steer connect
- Comes in single and double spear configurations to maximize load lifting
- Designed to economically and quickly replace damaged main spears
- One-year warranty for peace of mind



SPECIFICATIONS

SPEAR FEATURES	SINGLE SPEAR	DOUBLE SPEAR
Connector Type	Skid Steer	
Spear Number	1	2
Rated Capacity (lb) @ 23.5 (in) Elevation	3500	4000
Spear Length (in)	49.25	
Usable Spear Length (in)	42.5	
Spear Diameter (in)	1.78	
Replaceable Spear(s)	Yes	
Weight	152	184
Warranty	1-Year Limited	
SKU No.	AMIABP100	AMIABP200
TRACTOR COMPATIBILITY	SINGLE SPEAR	DOUBLE SPEAR
2638 ^[2]	X	
2645 ^[2]	X	
2660 ^[2]	X	
2670 ^[2]	X	
3640	X	
3650	X	
4540 2WD / 4WD	X	
4550 4WD	X	
6065 / 6075	X	X
7085 / 7095	X	X
8090 / 8100	X	X
9110 / 9125	X	X

^[2] Bale weight not to exceed loader lift capacity



RAKE GRAPPLES

SNATCH AND SEIZE ACCUMULATED DEBRIS

The Mahindra mGrip Compact rake grapples are great for ripping up and removing roots, stumps, and other debris like stone or concrete while leaving the dirt where it belongs. They also excel at demolition and carry out quick work when transporting timbered logs, precast pipe, and other bulky material.

FEATURES & BENEFITS

- Reduce downtime using its quick skid-steer connect
- Comes in 64- or 72-inch width configurations and long forks to maximize load capacity
- Hydraulic power with easy-to-grease pivot pins for years of dependability
- One-year warranty for peace of mind



SPECIFICATIONS

GRAPPLE FEATURES	MGRIP COMPACT 64	MGRIP COMPACT 72
Connector Type	Skid Steer & Third Function	
Overall Height (in)	44.8	
Overall Length (in)	22.8	
Grapple Width (in)	59.1	68.2
Rake Width (in)	64.5	73.7
Grapple Opening (in)	54.6	
Tooth Position (in)	22.4	
Tine Spacing (in)	15.75	14.5
Weight (lb)	446	495
Warranty	1-Year Limited	
SKU No.	AMIARC064	AMIARC072
TRACTOR COMPATIBILITY	MGRIP COMPACT 64	MGRIP COMPACT 72
1626	X	
1635	X	
1640	X	
2638	X	
2645	X	
2660		X
2670		X
3640		X
3650		X
4540 2WD / 4WD		X
4550 4WD		X



JAWZ™ GRABBING TOOL

UPROOT TREES, ROCKS, AND OTHER BURIED MATERIALS

With its hydraulic locking jaws, the Mahindra JAWZ grabbing tool forcefully snatches up invasive trees, shrubs, and roots in a single pass, thereby eliminating the need to spray herbicides, cut down trees, or burn stumps. It's a beast for building demolition too, including removing footings. Some customers use the JAWZ to relocate large rocks, boulders, logs, fence posts, and railroad ties.

FEATURES & BENEFITS

- Ideal for farmers, ranchers, contractors, landscapers, and forestry management
- Vegetation is removed in a single pass
- Edge pattern enhances gripping ability for irregular objects
- Dual, hydraulic cylinders apply equal pressure while maximizing lifting pressure
- Hardened T1 steel fingers (aka pinchers) for extracting onerous objects in heavy-duty applications
- One-year warranty for peace of mind

SPECIFICATIONS

GRABBER FEATURES	JAWZ GRABBING TOOL
Connector Type	Skid Steer & Third Function
Weight (lb)	550
Overall Height (in)	19
Overall Length (in)	41
Overall Width (in)	47
Maximum Jaw Opening (in)	33
Maximum Lift Weight (lb) ^[3]	Up to 3,000
Warranty	1-Year Limited
SKU No.	ATIJAWZ
TRACTOR COMPATIBILITY	JAWZ GRABBING TOOL
1626	X
1635	X
1640	X
2638	X
2645	X
2660	X
2670	X
3640	X
3650	X
4540 2WD / 4WD	X
4550 4WD	X
6065 / 6075	X
7085 / 7095	X
8090 / 8100	X

[3] Maximum lift depends on tractor model loader lift capacity



GRAPPLE ADD-ON

ECONOMICAL WAY TO MAKE A BUCKET MORE USEFUL

If you need a grapple for large, bulky objects, consider this implement. With a single tool, dig out a pond or level a dirt road, haul and broadcast small materials like pea gravel, rock, and dirt and grab unwieldy items like stumps, logs, and limbs.

FEATURES & BENEFITS

- A standard, 78-inch loader bucket has grapple tines attached to it
- Dual hydraulic cylinders for powerful grip
- 3/4-inch heavy-duty steel jaws open wide to securely grab bulky material
- Hydraulic hoses and couplers included
- One-year warranty for peace of mind

SPECIFICATIONS

GRAPPLE FEATURES	GRAPPLE ADD-ON
Connector Type	Skid Steer & Third Function
Bucket Width (in)	78
Tine Qty	4
Tines Thickness (in)	3/4
Hydraulic Cylinders	2
Warranty	1-Year Limited
SKU No.	KBGA0
TRACTOR COMPATIBILITY	GRAPPLE ADD-ON
6065 / 6075	X
7085 / 7095	X
8090 / 8100	X
9110 / 9125	X



4-IN-1 BUCKETS

TACKLE ALMOST ALL SITE-WORK WITH ONE TOOL

Why buy multiple implements for cleanup, grading, scraping, grappling, dozing, and brush removal when you can buy just one that does it all? Introducing the Mahindra 4-in-1 Bucket, a multi-tool comprising a bucket, a grapple, a dozier, and a scraper. Use the loader bucket to load, move and broadcast materials like pea gravel, mulch or dirt using the bottom dump feature. Use the grapple to clamp large bulky items like boulders, concrete footings, or logs. Push away unwanted brush and other debris using the dozier configuration. And level and contour your property with the scraper blade.

FEATURES & BENEFITS

- Single-bevel, scraper blade bolts on for easy replacement
- Front and back grapple edges are double-beveled and bolt on for easy rotation and replacement
- Hydraulic hoses and couplers included
- One-year warranty for peace of mind



SPECIFICATIONS

BUCKET FEATURES	5 FT	6 FT
Width (in)	60.96	72.96
Height (in)	27.32	27.32
Length (in)	34.47	34.47
Clam Length (in)	23.06	23.06
Back Blade Length (in)	12.36	12.36
Clam Opening (in)	34.64	34.64
Operating Pressure (psi)	2250	2250
Clamping Force (lb)	2354	2354
Weight (lb)	585	655
Heaped Capacity (cu-ft)	12.23	17.23
Cylinder Dimensions (in)	Bore 2.00 / Stroke 7.50 / Rod Diameter 1.12	
Warranty	1-Year Limited	
SKU No.	ATIB4IN160	ATIB4IN172
TRACTOR COMPATIBILITY	5 FT	6 FT
2638	X	
2645	X	
2660	X	
2670	X	
3640	X	X
3650	X	X
4540 2WD / 4WD	X	X
4550 4WD	X	X
6065 / 6075		X



ROCK BUCKETS

REMOVE SIZABLE DEBRIS WHILE PRESERVING SOIL

Easily rake, pile and haul away unwanted materials using the Mahindra rock bucket. It's a heavy-duty tool for quickly sifting soil while collecting rocks, roots, tree limbs, stumps, building scraps, landscaping waste, and other debris on your property or construction site.

FEATURES & BENEFITS

- Great for rock yards, lumber yards, construction sites, box stores, and warehouses
- Heavy-duty, set-up and welded tube framing
- 3-inch tine spacing to easily sifts dirt while capturing rocks and other debris
- One-year warranty for peace of mind

SPECIFICATIONS

BUCKET FEATURES	55 IN COMPACT	66 IN	75 IN
Connector Type	Skid Steer		
Overall Width (in)	55.3	65.9	74.4
Overall Depth (in)	43		
Overall Height (in)	22		
Tine Spacing (in)	3		
Tine Diameter (in)		1.125	
Number of Tines	18	22	25
Weight (lb)	300	625	692
Warranty	1-Year Limited		
SKU No.	ATIRB55C	ATIRB663	ATIRB753
TRACTOR COMPATIBILITY	55 IN COMPACT	66 IN	75 IN
Max 25XL	X		
Max 26XLT	X		
1626	X	X	
1635	X	X	
1640	X	X	
2638		X	
2645		X	
2660		X	X
2670		X	X
3640		X	X
3650		X	X
4540 2WD / 4WD		X	X
4550 4WD		X	X
6065 / 6075			X
7085 / 7095			X
8090 / 8100			X



STANDARD-DUTY ROTARY CUTTERS

CLEAR BRUSH & GRASS ON YOUR SMALL ESTATE

The Mahindra standard-duty rotary cutter is ideal for small acreage. Easily mow down tall grass, thickets, and new growth saplings in paddocks, fields, woods, and footpaths. It comes with lots of options, including a slip clutch and front and rear chains, for more abusive environments. And as a testament to its durability, it's backed by a strong warranty.

FEATURES & BENEFITS

- Fully-welded, 11-gauge steel deck with replaceable skid shoes for long product life
- 40 hp gearbox with a 5-year limited warranty
- Choose shear bolt or slip clutch
- Cuts up to 1.5-inch diameter trees
- Front and rear chain guards on some models



SPECIFICATIONS

CUTTER FEATURE	4 FT								5 FT								6 FT															
Connection Type	Top Link Flexible																															
Hitch Category	1																															
Quick-hitch Compatible	Yes																															
Cutting Height (in) ^[4]	2.5 – 8.0																															
Cutting Capacity Diameter (in)	1.5																															
Deck Thickness (ga)	11																															
Side Bands	HD 7-inch Channel																															
PTO Drive Shaft	Series 4																															
Stump Jumper	Pan																															
Gear Box (hp)	40 HP																															
Wheels	(1) Solid Laminated																															
Hub	Lubricating																															
Skid Shoes	Replaceable																															
Weight (lb)	390								470								550															
Shear Pin	X	X	X	X					X	X	X	X					X	X	X	X					X	X	X	X				
Slip Clutch					X	X	X						X	X	X	X					X	X	X	X					X	X	X	X
Front/Rear Chain Guards		X		X		X	X		X		X		X		X		X		X		X		X		X		X		X		X	
Warranty	5-year limited warranty for Gearbox; 1-year limited for other components																															
SKU No.	KRCSD484DSP	KRCSD484SPCG	KRCSD48SP3	KRCSD48SPCG3	KRCSD484DSC	KRCSD484DSCCG	KRCSD48SCCG3	KRCSD604DSP	KRCSD604SPCG	KRCSD60SP3	KRCSD60SPCG3	KRCSD604DSC	KRCSD604DSCCG	KRCSD60SCCG3	KRCSD724DSP	KRCSD724SPCG	KRCSD72SP3	KRCSD72SPCG3	KRCSD724DSC	KRCSD724DSCCG	KRCSD72SCCG3	KRCSD72SCCG3										
TRACTOR COMPATIBILITY	4 FT								5 FT								6 FT															
eMax 20S/22L	X	X	X	X	X	X	X																									
eMax 25L	X	X	X	X	X	X	X																									
Max 25XL	X	X	X	X	X	X	X																									
Max 26XLT	X	X	X	X	X	X	X																									
1626								X	X	X	X	X	X	X																		
1635								X	X	X	X	X	X	X																		
1640								X	X	X	X	X	X	X																		
2638								X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
2645								X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
2660															X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
2670															X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
3640															X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
3650															X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
4540 2WD / 4WD															X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	
4550 4WD															X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	

[4] Uses 3-inch offset blades



MEDIUM-DUTY ROTARY CUTTERS

CLEAR BRUSH & GRASS ON YOUR MEDIUM-SIZE PROPERTY

Medium-size property owners, including farmers and hunt clubs, rely on the Mahindra medium-duty rotary cutter to cut down overgrown brush, dense vegetation, and 2-inch diameter trees in pastures and woodlands, shooting lanes, and trails. While classified as medium-duty, it boasts heavy-duty components like a high-horsepower gearbox, an overbuilt stump jumper, an optional slip clutch, and a stellar warranty.

FEATURES & BENEFITS

- Fully-welded, 11-gauge steel deck with replaceable skid shoes for long product life
- 90 hp gearbox with a 5-year limited warranty
- Choose shear bolt or slip clutch
- Cuts up to 2-inch diameter trees
- Front and rear chain guards on some models



SPECIFICATIONS

CUTTER FEATURES	5 FT			6 FT				
Connection Type	Top Link Flexible							
Hitch Category	1 Clevis Type							
Quick-hitch Compatible	Yes							
Cutting Height (in) ^[4]	2.5 – 8.0							
Cutting Capacity Diameter (in)	2							
Deck Thickness (ga)	11							
Side Bands	HD 7-inch Channel							
PTO Drive Shaft	Series 4							
Stump Jumper	5/8-inch Solid							
Gear Box (hp)	90							
Wheels	[1] Solid Laminated							
Hub	Lubricating							
Skid Shoes	Replaceable							
Weight (lb)	620			755				
Shear Pin	X			X				
Slip Clutch		X	X		X	X	X	X
Front/Rear Chain Guards			X			X		X
Warranty	5-year limited warranty for Gearbox; 1-year limited for other components							
SKU No.	KRCMD60SP	KRCMD60SC	KRCMD60SCCG	KRCMD72SP	KRCMD72SC	KRCMD72SCCG	KRCMD72SC2TW	KRCMD72SC2TWCG
TRACTOR COMPATIBILITY	5 FT			6 FT				
1626	X	X	X					
1635	X	X	X					
1640	X	X	X					
2638	X	X	X					
2645	X	X	X	X	X	X	X	X
2660				X	X	X	X	X
2670				X	X	X	X	X
3640				X	X	X	X	X
3650				X	X	X	X	X
4540 2WD / 4WD				X	X	X	X	X
4550 4WD				X	X	X	X	X

[4] Uses 3-inch offset blades



HEAVY-DUTY ROTARY CUTTERS

CLEAR BRUSH & GRASS ON YOUR LARGE FARM

Large property owners including livestock and mixed farms, nurseries, orchards, and hunt clubs will appreciate a Mahindra heavy-duty rotary cutter. It takes the abuse of rocks and stumps while clearing overgrown brush, dense vegetation, and saplings up to 3 inches — thanks to its indestructible housing, overbuilt gearbox and slip clutch. It comes with a rock-solid warranty, too, so you can confidently mow your fields into pristine condition year after year.

FEATURES & BENEFITS

- Available in 3-pt lift and pull configurations
- Lift models CAT 1 or 2 quick-hitch compatible
- Fully-welded, 7-gauge steel deck with replaceable skid shoes for long product life
- Cuts up to 3-inch diameter trees
- Front and rear chain guards on some models
- Gearboxes with 5-year limited warranty



SPECIFICATIONS

CUTTER FEATURES	3-PT LIFT							PULL				
Size (ft)	6		7		8		10	7	8		10	
Connection Type	3-pt Lift							Center Pull Self Leveling				
Transport Width	—		—		98		122	90	102		126	
Hitch Category	2					1 or 2		—				
Quick-hitch Compatible	Yes							—				
Cutting Height (in) ^[4]	2 – 10							2 – 12				
Cutting Capacity Diameter (in)	3											
Deck Thickness (ga)	7											
Side Bands	HD 8-inch Channel											
Minimum Engine Power (hp)	—		—		42		52	45	55		60	
Hydraulic Cylinder with Hose								3 x 1.25 x 8				
PTO Drive Shaft (Slip Clutch)	Series 6				Series 5			Constant Velocity				
Center Drive Shaft	—		—		Shock Coupler-Protected			—		Shock Coupler-Protected		
Stump Jumper	5/8-inch Solid		3/4-inch Solid		5/8-inch Thick & Round							
Center Gear Box (hp)	90				100							
Outboard Gear Boxes (hp)	—		(1) 90		(2) 90							
Wheels	(2) Solid Laminated											
Spindle Hubs	Ball Bearing											
Skid Shoes	Replaceable											
Tongue Jack								Fold-Up Removable				
Weight (lb)	1030		1220		1370		1590	1650	1800		2090	
Shear Pin												
Slip Clutch	X	X	X	X	X	X	X	X	X	X	X	X
Front/Rear Chain Guards		X		X		X		X		X		X
Warranty	5-year limited warranty for Gearbox; 1-year limited for other components											
SKU No.	KRCHD72SC	KRCHD72SCCG	KRCHD84SC	KRCHD84SCCG	KRCHD96SC	KRCHD96SCCG	KRCHD120SCLC	KRCHD84DWSCCG	KRCHD96DWSC	KRCHD96DWSCCG	KRCHD120DWSC	KRCHD120DWSCCG
TRACTOR COMPATIBILITY	3-PT LIFT							PULL				
2660	X	X	X	X								
2670	X	X	X	X	X	X		X	X	X		
3640												
3650	X	X	X	X								
4540 2WD / 4WD												
4550 4WD	X	X										
6065 / 6075	X	X	X	X	X	X	X	X	X	X	X	X
7085 / 7095					X	X	X		X	X	X	X
8090 / 8100							X				X	X

[4] Uses 3-inch offset blades



FLEX WING ROTARY CUTTERS

THE PRO CHOICE FOR CONTOUR-CUTTING BRUSH AND GRASS

The Mahindra F-Series flex-wing rotary cutters are ideal for airports, campuses, estates, farms, parks, orchards, and roadsides. The Flex-Wing deck design lets you cut on rolling terrain without having to make multiple passes — something fixed-deck cutters can only dream of. They come in three widths, including 10, 12, and 15 feet. They are engineered to be powerful and heavy-duty and have a warranty to match.

COMMON FEATURES & BENEFITS

- Safety features include deflectors and/or chain guards to protect people, passing cars, and buildings from rocks and debris
- Smooth, thick wall decks for easy cleanup, preventing rust, and long life
- Replaceable, anti-scalping skid shoes for excellent ground contouring and long-lasting deck life
- Heavy-duty turn buckles for fewer breakdowns and less stress
- Easy-lift composite hood for quick maintenance
- Best-in-class Lucas Oil® for reduced gearbox wear, friction, drag, and heat
- 5- or 6-year limited gearbox warranty for peace-of-mind



F-10

We designed the F-10 Flex Wing rotary cutter to operate with smaller compact and utility tractors displacing 25 or greater horsepower at the PTO. With its flexible 120-inch cutting width, you'll uniformly cut thick grass, dense brush, and saplings in no time.

FEATURES & BENEFITS

- Works with PTOs discharging 25 – 60 hp
- Transport width fits through an 8-ft gate
- Average mowing rate of 4 MPH
- EZ-Loc collar for fast hookup
- 1- to 15-inch cutting height
- 2-inch diameter cutting capacity

F-12

With a more compact design than our F-10 model, The F-12 Flex Wing rotary cutter makes narrow turns and close cuts around trees, thanks to its pivoting hitch and form-fitting tires. And it's unique wing-bar blade keeps it lightweight while protecting the gearbox output shaft.

FEATURES & BENEFITS

- Works with PTOs discharging 35 – 60 hp
- Transport width fits through a 9-ft gate
- 12-ft wide cutting deck
- Bi-directional pivoting hitch for impressive short turning radius in tight spaces
- 2- to 12-inch cutting height
- 1.5-inch diameter cutting capacity

F-15

For the Mahindra F-15 Flex Wing rotary cutter, we offer the off-road Farmer and the on-road Pro models. The Pro comes with deck rings to protect the cutter and gearbox shaft from asphalt and other unexpected obstacles. Suited for utility tractors, the F-15 offers a smooth top and bottom deck with dual-cut chambers, heavy-duty gearboxes, and a coil-spring suspension for fast and productive cutting.

FEATURES & BENEFITS

- Works with PTOs discharging 50 – 130 hp
- Transport width fits through a 10-ft gate
- 15-ft wide cutting deck
- Heavy-duty blade carrier and CAT5 CV main gearbox for harsh applications
- Coil-spring suspension for protection over bumpy terrain and operator comfort
- 2- to 14-inch cutting height
- 2.5-inch diameter cutting capacity

SPECIFICATIONS

CUTTER FEATURES	F-10	F-12	F-15 FARMER	F-15 PRO
SKU No.	RHIMF103000	RHIMF123000	RHIMF15F3000	RHIMF15P3000
Cutting Width (in)	120	144	180	180
Transport Width (in)	93	97	116	116
Transport Height (in)	68	65	75	75
Overall Width (in)	126	155	187	187
Overall Length (in)	162	148	172	172
Cutting Height (in) ^[5]	1 – 15	2 – 12	2 – 14	
Height Adjustment	Hydraulic Cylinder	Hydraulic Cylinder	Hydraulic Cylinder	
Jack Stand	Standard			
Hitch Pull-type	Parallel Clevis	Pull-Swivel	Clevis	
Blade Carrier	Infinity Steel			
Blades (in)	1/2 x 3 High Lift		1/2 x 4 Parallel Lift	
Blade Overlap (in)	6			
Tractor PTO Range (hp)	25 – 60	35 – 60	50 – 130	
Gearbox: Power Divider (hp) ^[6]	160 HP			
Gearbox: Center & Wing (hp) ^[6]	65		130	
Gearbox Oil (85W-140)	Factory-filled Lucas Oil			
Output Shaft Diameter (in)	1-9/16		2	2
Blade Tip Speed: Center 540 rpm (fpm)	13,028	14,504	14,861	14,861
Blade Tip Speed: Wing 540 rpm (fpm)	13,680	13,925	14,861	14,861
Blade Tip Speed Center 1000 rpm (fpm)	—	—	15,570	15,570
Blade Tip Speed Wing 1000 rpm (fpm)	—	—	15,776	15,776
Cutting Diameter Capacity (in)	2	1-1/2	2-1/2	
Driveline Protection	Slip Clutch			
Driveline ASABE: Main	CAT 4 CV	CAT 4 Equal Angle	Cat 5 CV	
Driveline ASABE: Wing	CAT 3 SC	CAT 3	Cat 4	
Deck Thickness: Center (ga)	12	12 Top / 10 Bottom	10 Top / 7 Bottom	
Deck Thickness: Wing (ga)	12	12 Top / 12 Bottom	10 Top / 10 Bottom	
Side Skirt Thickness x Height (in)	1/4 x 10	1/4 x 11-1/2	1/4 x 12-3/8	
Tires & Wheels	Foam-filled			Laminated
Wing Lift (in)	Hydraulics		Mechanical Level Lift	
Wing Flex: Up / Down (Degrees)	90° / 22°	88° / 25°	87° / 25°	
Safety Tow Chain	Standard	Standard		
LED Light Kit	—	Standard		
Safety	Deflectors or Chain	Chain Guards	Deflectors and/or Chains	
Tongue Weight (lb)	720	748	1,430	
Approximate Weight (lb)	2,190	2,750	4,290	
Gearbox Warranty	5-year Limited ^[7]		6-year Limited (w/ 2-year seals)	
Warranty	1-year Full			

^[5] Cutting height dependent on tire size ^[6] Gearbox ratings based on field performance ^[7] For non-commercial use only

SPECIFICATIONS

TRACTOR COMPATIBILITY	F-10	F-12	F-15 FARMER	F-15 PRO
SKU No.	RHIMF103000	RHIMF123000	RHIMF15F3000	RHIMF15P3000
2645	X			
2660	X	X		
2670	X	X		
3640				
3650	X	X		
4540 2WD / 4WD				
4550 4WD	X			
6065 / 6075	X	X	X	X
7085 / 7095			X	X
8090 / 8100			X	X
9110 / 9125			X	X



FINISH MOWERS

MAINTAIN A WELL-MANICURED LAWN

Mahindra finish mowers are ideal for businesses, estates, farms, hospitals, orchards, and parks. They transform high grass into a groomed, professional cut lawn. Anti-scalp features include four oversized wheels to ensure even cutting and a floating hitch to hug the contoured terrain. They are easily adjustable and low maintenance machines.

FEATURES & BENEFITS

- Available in 4 to 7-ft cutting widths
- Adjustable tires with 360-degree rotation for 4-wheel traction and to help prevent scalping hills and depressions
- Built heavy-duty, with few parts, for low maintenance
- Smooth deck for easy cleanup and to prevent rust
- 5-year limited gearbox warranty

SPECIFICATIONS

MOWER FEATURES	4 FT	5 FT	6 FT	7 FT
PTO Horsepower Range (hp)	14 – 23	23 – 32	32 – 40	35 – 50
Weight (lb)	420	440	500	850
Hitch Category	1			
Hitch Type	3-pt floating (Adjustable front & rear)			
Wheel Qty	4			
Wheel Rotation	360°			
Discharge	Rear			
Anti-Scalp	Yes			
Spindles	Lubricating with check valves			
Protection	Shear Bolt			
Offset	Horizontal; Adjustable			
Blade Qty	3			6
External Belt Qty	2			
Gearbox Warranty	5-year limited			
Warranty	Residential, semi-commercial, regular commercial use: 1 year			
SKU No.	KFM48	KFM60	KFM72	KFM84
TRACTOR COMPATIBILITY	4 FT	5 FT	6 FT	7 FT
eMax 25L	X			
Max 25XL	X	X		
Max 26XLT	X	X		
1626		X	X	
1635		X	X	
1640		X	X	
2638		X	X	
2645			X	
2660			X	X
2670			X	X
3640			X	X
3650			X	X
4540 2WD / 4WD			X	X
4550 4WD			X	X
6065 / 6075				X



SHREDDERS

MULCH CROPS, BRUSH, GRASS, AND LIMBS

Mahindra mShred flail shredders are high-capacity mulching machines for a pro-finish cut. You'll see them at airports, campuses, estates, farms, golf courses, parks, and orchards. Many of our customers use them for clearing brush, pruned branches, and post-harvest row crops like cotton, corn stalks, milo, and rice. Our shredders are built to last, as evidenced by our solid 2-year warranty.

FEATURES & BENEFITS

- Tried and true Y-type cutting knives evenly mulch organic matter, returning nutrients to the soil faster
- 1.0- to 4.75-inch cutting height
- Shredder will not sling debris like a rotary cutter but has chain guards for operator and tractor protection just in case
- Heavy-duty gearbox and frame with 4-gauge shredding hood ensures years of trouble-free performance
- Rear roller helps prevent scalping while creating a classic stripe effect
- 2-year warranty for peace-of-mind



SPECIFICATIONS

SHREDDER FEATURES	MSHRED 260	MSHRED 310
Cutting Width (ft)	8.5	10.5
Min/Max PTO (hp)	50 – 80	55 – 80
Weight (lb)	2500	2800
Hitch Category	2	
Hitch Type	3-pt Lift	
PTO Speed 540	540	
PTO Category	T7	
Remote Valve Required	No	
Hood Thickness (ga)	4	
Rotor Size (in)	23.75	
Standard Rotor Speed	422	
Blades Type	Y	
Blade Qty	56	72
Blade Length (in)	7.9	
Min – Max Cut Height (in)	1 – 4.75	
Overall Height (ft)	3.5	
Overall Length (ft)	4.5	
Overall Working Width (ft)	9	11
Warranty	2 Years Full	
SKU No.	HIS30000254	HIS30000250
TRACTOR COMPATIBILITY	MSHRED 260	MSHRED 310
2670	X	
3640		
3650		
4540 2WD / 4WD		
4550 4WD		
6065 / 6075	X	X
7085 / 7095	X	X
8090 / 8100	X	X
9110 / 9125		X



BOX SCRAPERS

SPREAD AND LEVEL AGGREGATES

Mahindra box scrapers come in handy for ripping ground material, and leveling, grading, and backfilling materials like pea gravel and dirt. You've probably seen them used for construction site work, leveling and maintaining driveways, garden prep work, repairing holes, and contouring property. We build our box scrapers rugged and quick to adjust and maintain. Optional scarifier shanks break up compacted soil, while the box holds and channels dirt and aggregate uniformly where you want it.

FEATURES & BENEFITS

- Works with 17 – 60 hp tractors
- CAT 1, quick-hitch connection using clevis pins for easy hookup
- Choose from 4- to 6-ft wide standard-duty models or 5- to 8-ft wide heavy-duty configurations
- Front and rear curved blades are ideal for digging and made heavy-duty, reversible, and replaceable
- Reinforced scarifier slots for long-lasting tool life
- Wide box holds, distributes, and grooms large volumes of material in less time
- One-year warranty for peace of mind



SPECIFICATIONS

SCRAPER FEATURES	STANDARD-DUTY			HEAVY-DUTY			
Width (ft)	4	5	6	5	6	7	8
Max PTO (hp)	55						
Quick-hitch Compatible	Yes						
Hitch Category	1						
Hitch Type	3-pt Lift						
Weight (lb)	770	820	830	900	1000	1150	1300
Slots	Reinforced for prolonged use without splaying						
Shanks	Heavy-duty, replaceable tips and adjustable						
Tips	Hardened, replaceable steel						
End Plates (in)	20 x 14.5 x 1/4 thick			24 x 16 x 1/2 thick			
Cutting Blades	3/8-inch thick x 6-inch tall x various width of unit						
Warranty	Residential, semi-commercial, regular commercial use: 1 year						
SKU No.	KBSSD4	KBSSD5	KBSSD6	KBSHD5	KBSHD6	KBSHD7	KBSHD8
TRACTOR COMPATIBILITY	STANDARD-DUTY			HEAVY-DUTY			
eMax 20S/22L	X						
eMax 25L	X	X					
Max 25XL	X	X					
Max 26XLT	X	X					
1626		X					
1635		X					
1640		X					
2638		X					
2645			X	X			
2660						X	
2670							
3640			X	X	X	X	
3650			X		X	X	
4540 2WD / 4WD			X	X	X	X	
4550 4WD				X	X	X	
6065 / 6075						X	X



TILLERS

TURN OVER, BREAK DOWN, MIX, AND WEED SOIL

We have Mahindra tillers for everyone, from the novice to the commercial farmer. They're ideal for home gardening, landscaping, nurseries, orchards, and agriculture. They efficiently increase soil aeration, which helps crops root quicker and grow deeper, improving overall plant health. Our tillers boast hefty frames, thick gauge shrouds, overbuilt gearboxes, forgiving slip clutches, robust flanges and high-strength blades. All backed by a 5-year gearbox and 2-year comprehensive warranty.

COMMON FEATURES & BENEFITS

- Simple 3-pt Lift hookup and parking stand
- Heavy-duty frame, hood, gearbox, and slip clutch ensure long product life
- C blades for rocky and densely-packed soil conditions and chopping of sod and roots
- Adjustable rear hood to guarantees consistent soil size and bed depth
- Adjustable and replaceable skid shoes for long product life
- 2-year comprehensive warranty for peace-of-mind



STANDARD-DUTY TILLERS

The Mahindra mTill 120, 150, and 180 home-use rotary tillers pair with subcompact, compact, and utility tractors that displace 18 to 55 hp at the PTO. They have category O fittings for sub-compact models and class 1 for more powerful tractors.

FEATURES & BENEFITS

- CAT 1 quick-hitch compatible
- 4-, 5-, and 6-ft wide tillers with 6.5- or 7.5-inch digging depth, depending on model
- Side-gear drive to ease mechanical stress, reduce heat buildup and extend gearbox and oil life

MEDIUM-DUTY TILLERS

Mahindra mTill 210 and 240 rotary tillers are intended for commercial and farming applications, while engineered for utility tractors displacing 50 to 90 hp at the PTO. Both models come equipped with a husky 20-inch rotor equipped with 48 – 54 heat-treated blades for prolonged life in harsh conditions.

FEATURES & BENEFITS

- CAT 2 quick-hitch compatible
- Half-ton implement with rigid steel frame helps reduce bouncing during cultivation
- mTill 210 has optional 4-speed gearbox for ground condition adjustments
- 7- and 8-ft wide tillers with 4.75- to 8-inch digging depth
- Stout 8-gauge shroud and rear hood to distribute soil evenly

HEAVY-DUTY TILLERS

The Mahindra mTill Extreme 250 rotary tiller is utilized in commercial and farming environments and engineered for utility tractors displacing 70 to 100 hp at the PTO. It comes equipped with 54 case-hardened blades and a four-speed gearbox for ground condition adjustments. What's more, it comes with a massive, 15-inch diameter, rear cage roller to break up soil while secondary tilling.

FEATURES & BENEFITS

- CAT 2 or 3 quick-hitch compatible
- 3000 lb. implement keeps it from bouncing for cultivating of the most stubborn soil
- 8-ft wide tiller with 4.75- to 8-inch digging depth
- Heavy-duty, 4-gauge shroud and rear hood to distribute soil evenly

SPECIFICATIONS

TILLER FEATURES	MTILL 120	MTILL 150	MTILL 180	MTILL 210	MTILL 210 4-SPEED	MTILL 240	MTILL 250 EXTREME
SKU No.	AMIART120	AMIART150	AMIART180	HIS30000172	HIS30000179	HIS30000181	HIS30003522
Duty Cycle	Standard			Medium			Heavy
Min/Max PTO (hp)	18 – 35	25 – 45	40 – 55	50 – 90		55 – 90	70 – 100
Operating Width (in)	48.0	62.0	74.0	82.0		94.0	98.0
Overall Length (in)	26.9	27.6		33.0			72.0
Overall Height (in)	32.3	33.1		42.0			51.0
(Min/Max) Working Depth (in)	6.5	7.5		4.75 – 8.0			
Weight (lb)	356	488	626	1125	1150	1267	2976
Shipping Width (in)	52.2	67.1	79.3	7.42		8.75	
Hitch Type	3-pt Lift						
Hitch Category	0 or 1	1		2			2 or 3
Quick-hitch Compatible ^[B]	Yes (CAT I only)			Yes			
Parking Stand	Yes						
Drive Type	Gear						
PTO Speed (rpm)	540						
PTO Category	1			M8			
Driveline Protection	Slip Clutch						
Remote Valve Required	No						
Hood Thickness (ga)	5.5			8			4
Rotor Size (in)	15.8	18.3		20			19
Rotor Speed (rpm)	240			249	203 / 328 264 / 310	249	203 / 328 264 / 310
Blades Type	C						
Blade Qty	20	42	54	48		54	
Flange Qty	5	7	9	9		10	
Blade Length (in)	9.5			7			
Depth Control	Via Skid Shoes						
Rear Roller Type	—						Cage
Rear Roller Diameter (in)	—						15
Gearbox Warranty	5-years Limited						
Warranty	2-years Full						

[B] Must Meet ASABE Specifications

SPECIFICATIONS

TRACTOR COMPATIBILITY	MTILL 120	MTILL 150	MTILL 180	MTILL 210	MTILL 210 4-SPEED	MTILL 240	MTILL 250 EXTREME
SKU No.	AMIART120	AMIART150	AMIART180	HIS30000172	HIS30000179	HIS30000181	HIS30003522
eMax 25L	X						
Max 25XL	X						
Max 26XLT	X						
1626		X					
1635		X					
1640		X					
2638		X					
2645		X	X				
2660			X				
2670			X	X			
3640			X				
3650			X				
4540 2WD / 4WD			X				
4550 4WD			X				
6065 / 6075				X	X		
7085 / 7095				X	X	X	X
8090 / 8100					X	X	X
9110 / 9125					X	X	X



MEDIUM-DUTY DISC HARROWS

ECONOMICALLY PREP SOIL VIA PULLING POWER

Mahindra medium-duty disc harrows are a budget-friendly alternative to more expensive cultivators. They may not have all the bells and whistles, but they're engineered to get your primary tilling done. There are six configurations, all equipped with hardened notched discs and rigid frames to penetrate, chop, bust up, turn over, and aerate compacted soil.

FEATURES & BENEFITS

- Category 1, quick-hitch compatible
- Heavy-duty 2.5-inch tube frame
- Equipped with 16, 18, or 20 replaceable discs
- Available in 54-, 66-, 84-, 90- and 96-inch configurations
- Sealed self-aligning bearings keep dirt out and improve product life

SPECIFICATIONS

HARROW FEATURES	4.5 FT	5.5 FT	7 FT	7.5 FT	8 FT	
Overall Width (in)	54	66	84	90	96	
Min/Max PTO (hp)	24 - 40		30 - 50	35 - 55		
Hitch Category	1					
Hitch Type	3-pt Lift					
Quick-hitch Compatible	Yes					
Disc Diameter (in)	16	20		24		
Disc Qty	16	18	20			
Disc Spacing (in)	7			9	7	
Replaceable Discs	Yes					
Tube Frame	2.5					
Warranty	Residential, semi-commercial, regular commercial use: 1 year					
SKU No.	KDH16X16TUB	KDH16X18TUB	KDH20X18TUB	KDH20X20TUB7	KDH20X20TUB9	KDH24X20TUB
TRACTOR COMPATIBILITY	4.5 FT	5.5 FT	7 FT	7.5 FT	8 FT	
1626	X	X	X			
1635		X	X			
1640		X	X	X		
2638		X	X	X		
2645		X	X	X		
2660		X	X	X	X	
2670				X	X	
3640		X	X	X	X	
3650		X	X	X	X	
4540 2WD / 4WD		X	X	X	X	
4550 4WD		X	X	X	X	
6065 / 6075				X	X	
7085 / 7095				X	X	
8090 / 8100				X	X	



HEAVY-DUTY DISC HARROW

PREPARE SEEDBEDS VIA TRACTOR PULLING POWER

The Mahindra Quick-Till 320 generates primary and secondary tillage for seed-ready soil. It's ideal for crop or cattle farms utilizing large 100 to 140 hp utility tractors. It's built to last, equipped with a beefy hull, thick side deflectors, heavy-duty notched discs, and a rear roller with depth-control hydraulic lift and 0.3-inch thick teeth. Twenty-eight heavy-duty disks penetrate, chop, bust up, turn over, and aerate the most stubborn soil. The rear roller efficiently breaks down and flattens leftover clumpy topsoil to limit moisture dissipation and to create a uniform seedbed.

FEATURES & BENEFITS

- CAT 2 or 3 quick-hitch compatible
- 10.5-ft operating width for fast work
- 3.5- to 9.75-inch digging depth ideal for primary and secondary tillage
- Side deflectors for flow control and creating level finish
- 2-year comprehensive warranty for peace-of-mind



SPECIFICATIONS

HARROW FEATURES	QUICK-TILL 320
Min/Max Engine (hp)	100 – 140
Operating Width (ft)	10.5
Overall Length (ft)	7.75
Min/Max Working Depth (in)	3.5 – 9.75
Weight (lb)	3200
Frame Thickness (ga)	2
Transport Width (ft)	11.5
Transport Height (ft)	6.5
Disk Qty	28
Disk Diameter (in)	22
Disk Type	Notched
Disk Spacing (in)	8.75
Disk Bearing Type	Angular Contact
Hitch Type	3-pt Lift
Hitch Category	2 & 3
Remote Valves Required	2
Side Deflectors	Yes
Rear Roller Type	Notched Cage
Rear Roller Control	Hydraulic
Warranty	2-years Full
SKU No.	HIS30004482
TRACTOR COMPATIBILITY	QUICK-TILL 320
8090 / 8100	X
9110 / 9125	X



POWER HARROW

PREPARE SEEDBEDS VIA TRACTOR PTO

The Mahindra Total-Till 250 power harrow generates primary and secondary tillage, making perfect seedbeds. We engineered it for commercial and farming operations utilizing large utility tractors which displace 70 to 95 hp at the PTO. It's built heavy-duty, equipped with a strong hull, thick side deflectors, reliable gearbox and slip clutch, 2-speed rotors, high-strength blades, and a formidable packing roller. The bladed rotors move laterally — both clockwise and counter-clockwise — to bust up and loosen soil, drawing larger aggregate to the surface and burying top growth and weed seedlings deep below ground, inhibiting germination. The leveler's packing roller breaks down and flattens leftover clumpy topsoil to limit moisture dissipation and to create a uniform seedbed. And because it operates under PTO power, the Total-Till 250 functions moving or standing still, providing superior results in less time.

FEATURES & BENEFITS

- CAT 2 or 3 quick-hitch compatible
- 8-ft operating width makes fast work
- 6- to 11-inch digging depth ideal for primary and secondary tillage
- Heavy-duty gearbox backed by a 5-year limited warranty
- 2-year comprehensive warranty for peace-of-mind



SPECIFICATIONS

HARROW FEATURES	TOTAL TILL 250
Hitch Category	2 & 3
PTO Speed (rpm)	540
Min/Max PTO (hp)	70 – 95
Operating Width (ft)	8.17
Overall Height (ft)	4.67
Min/Max Working Depth (in)	6 – 11
Weight (lb)	2315
Transport Width (ft)	9.17
Flange Qty	10
Blade Qty	20
Hitch Type	3-pt Lift
Driveline Protection	Slip Clutch
Remote Valves Required	0
Depth Control	Via Roller
Rotor Qty	10
Rotor Speeds Settings	2
Rotor Speeds (rpm)	190 / 360
Side Deflectors	Yes
Rear Roller Type	Packer
Warranty	2-years Full
SKU No.	HIS30003318
TRACTOR COMPATIBILITY	TOTAL TILL 250
7085 / 7095	X
8090 / 8100	X
9110 / 9125	X



REAR BLADES

CONTOUR, LEVEL, BACKFILL, AND PUSH MATERIALS

Mahindra rear blades quickly move topsoil, gravel, snow, and other aggregates. They're ideal for grading landscapes, cleaning up worksites, improving roads, and removing driveway snow. All have heavy-duty frames, beefy steel moldboards that pivot 360°, stout reversible and replaceable cutting blades, and are quick-hitch compatible with parking stand. What's more, there are ten configurations to match up with your tractor size and usage level.

ECONOMY BLADE FEATURES & BENEFITS

- 4 to 6-ft widths with optional slider
- CAT 1 connection for sub-compact and compact utility tractors

STANDARD-DUTY BLADE FEATURES & BENEFITS

- 4 to 6-ft widths with optional slider
- CAT 1 connection for sub-compact and compact utility tractors

MEDIUM-DUTY BLADE FEATURES & BENEFITS

- 6-ft widths with optional ratchet offset
- CAT 1 connection for compact utility tractors

HEAVY-DUTY BLADE FEATURES & BENEFITS

- 7- and 8-ft widths with ratchet offset, tilt, and pivot for ditching or fence line grading
- CAT 1 and 2 connections for utility tractors



SPECIFICATIONS

BLADE FEATURES	FIXED ECONOMY			SLIDER ECONOMY		STANDARD-DUTY		MEDIUM-DUTY	HEAVY-DUTY		
	4	5	6	5	6	5	6	6	7	8	
Operating Width (ft)	4	5	6	5	6	5	6	6	7	8	
2WD Max Engine (hp)	24	25	28	25	28	40	40	46	80		
4WD Max Engine (hp)	20	20	23	20	23	40	40	38	65		
Hitch Type	3-pt										
Hitch Category	1								1 or 2		
Quick-hitch Compatible	Yes										
Moldboard Thickness x Height (in)	0.25 x 13.5			0.25 x 15.5				0.3 x 17.5			
Blade Thickness x Height (in)	0.5 x 6										
Blades	Reversible & Replaceable										
Forward/Reverse Angle Qty	5 / 5										
Optional Hydraulic Angling	No								Yes		
Offset Positions	—			5		—					
Left/Right Ratchet Offset	—							30° / 30°			
Pan Tilt (Degrees)	—			15°							
Parking Stand	—					Yes					
Weight (lb)	158	179	202	179	202	550	570	620	667	702	
Warranty	Residential, semi-commercial, regular commercial use: 1 year										
SKU No.	KEBSD4	KEBSD5	KEBSD6	KSB5	KSB6	KGBSD454DTLT	KGBSD640TLT	KBLMD6	KBLOS6	KBLHD7	KBLHD8
TRACTOR COMPATIBILITY	FIXED ECONOMY			SLIDER ECONOMY		STANDARD-DUTY		MEDIUM-DUTY	HEAVY-DUTY		
eMax 25L	X										
Max 25XL	X										
Max 26XLT	X										
1626		X	X	X		X					
1635		X	X	X	X	X	X	X	X		
1640		X	X	X	X	X	X	X	X		
2638		X	X	X	X	X	X	X	X		
2645			X		X		X	X	X		
2660								X			
2670										X	X
3640		X	X					X			
3650			X							X	
4540 2WD / 4WD			X		X		X	X	X		
4550 4WD			X		X			X			
6065 / 6075										X	X
7085 / 7095										X	X
8090 / 8100										X	X



LANDSCAPE RAKES

SIFT AND GROOM SOIL VIA TRACTOR PULLING POWER

Mahindra landscape rakes remove debris while conditioning soil and seedbeds. They're dependable spreading landscaping mulch and compost, grading gravel driveways, and beach grooming too. Our rakes are overbuilt with heavy gauge frames and tempered tines, easily displacing rocks, weeds, and roots while leaving soil where it belongs. 360-degree positioning controls debris purge flow to a single side when pulling or pushing rake. Optional gauge wheels (SKU No. KDK5010025) assist in keeping rake depth to the controlled level.

STANDARD-DUTY RAKE FEATURES & BENEFITS

- Heavy-duty 5/16-inch thick, 4-inch square tube frame
- 5/16-inch thick, 1-inch wide tempered steel tines
- CAT 1 quick-hitch compatible with parking stand

HEAVY-DUTY RAKE FEATURES & BENEFITS

- Heavy-duty 3/8-inch thick, 5- x 3-inch tube frame
- 5/16-inch thick, 1-inch wide tempered steel tines
- CAT 1 quick-hitch compatible with parking stand



SPECIFICATIONS

RAKE FEATURES	STANDARD-DUTY			HEAVY-DUTY		
Operating Width (ft)	4	5	6	6	7	8
Weight (lb)	461	523	588	588	650	726
Hitch Category	1					
Hitch Type	3-pt Lift					
Frame Tube (in)	5/16 thick x 4 x 4			3/8 thick x 5 x 3		
Forward/Reverse Angle Positions	4 / 4					
Tines (in)	5/16 thick x 1 wide tempered steel					
Warranty	Residential, semi-commercial, regular commercial use: 1 year					
SKU No.	KLRSD4	KLRSD5	KLRSD6	KLRHD6	KLRHD7	KLRHD8
TRACTOR COMPATIBILITY	STANDARD-DUTY			HEAVY-DUTY		
eMax 25L	X	X	X			
Max 25XL	X	X	X	X		
Max 26XLT	X	X	X	X		
1626		X	X	X		
1635		X	X	X		
1640		X	X	X	X	
2638		X	X	X	X	
2645			X	X	X	
2660				X	X	X
2670				X	X	X
3640			X	X	X	
3650				X	X	X
4540 2WD / 4WD			X	X	X	
4550 4WD			X	X	X	X
6065 / 6075					X	X
7085 / 7095					X	X



HARLEY POWER RAKES

PULVERIZE, GRADE, AND CULTIVATE SOIL VIA TRACTOR PTO

Mahindra Harley power rakes, intended for landscapers and turf professionals, use PTO power to remove debris while cultivating soil and seedbeds. Also, they're dependable for dethatching, leveling crowns, grading dirt or gravel roads, and worksite cleanup including clearing debris and finish-grading landscapes. Our commercial-grade rakes have beefy main frames, heavy-duty gearboxes and side-mounted gear drives, and indestructible, carbide-toothed drum. They quickly pulverize and sift the soil while expelling to the surface unwanted debris like rocks and grass clumps. They have hydraulic angle roll, removable side plates, two adjustable gauge wheels, and are backed by a solid warranty.

FEATURES & BENEFITS

- CAT 1 quick-hitch compatible
- Available in 6- and 7-ft raking widths
- Adjustable 6-inch roll back barrier controls particle size while expelling damaging debris
- 15-degree hydraulic angle roll for efficient windrowing when angled left or right
- Forward and backward drum rotation for maximum flexibility
- Adjustable gauge wheels for uniform digging depth



SPECIFICATIONS

RAKE FEATURES	6 FT	7 FT
Min/Max Engine (hp)	30 – 40	42 – 80
Hitch Category	1	1 or 2
Hitch Type	3-pt Lift	
Width (in)	81	93
Length (in)	48	56
Raking Width (in)	72	84
Raking Width Full Angle (in)	69	81
Roll-Back Barrier Range (in)	5/16 – 2-15/16	1-1/8 – 3-3/8
Angle Roll	15°	
Required Flow (gpm)	15 – 17	
Gauge Wheels	Independently-adjustable and foldable for storage	
Warranty	Residential, semi-commercial, regular commercial use: 1 year	
SKU No.	ATIHR6H3PT	ATIHR7H3PT
TRACTOR COMPATIBILITY	6 FT	7 FT
1640	X	
2638	X	
2645	X	
2660		X
2670		X
3640	X	X
3650		X
4540 2WD / 4WD	X	X
4550 4WD		X
6065 / 6075		X



LAND LEVELERS

RIP, FLATTEN AND GRADE SOIL ECONOMICALLY

Mahindra land levelers are an inexpensive tool for homeowners, landscapers, and farmers. They're tough enough to rip into rocky soil, level terrain, smooth dirt and gravel roads, and grading landscapes. They have heavy gauge frames and cutting blades for the most demanding tasks, and are ideal for subcompact, compact, and utility tractors up to 70 horsepower.

FEATURES & BENEFITS

- CAT 1 quick-hitch compatible
- Choose 5-, 6- or 7-ft widths
- Hefty frame and thick, heat-treated cutting blades for compact or rocky soil
- Commercial-duty, 3/8-inch thick, reversible cutting blade
- Reversible and replaceable skid shoes

SPECIFICATIONS

LEVELER FEATURES	5 FT	6 FT	7 FT
Min/Max Engine Rating (hp)	25 – 40	30 – 55	35 – 70
Quick Hitch Compatible	Yes		
Hitch Category	1 (Cleviss Pin)		
Weight (lb)	485	525	575
Overall Width (in)	60.5	72.5	84.5
Overall Length (in)	65		
Side Panel Dimensions (in)	59.5 length x 14 height x 3/16 thick		
Front Beam (in)	3.0 x 4.0 x 3/16 thick		
Rear Beam (in)	2.0 x 2.0 x 3/16 thick		
Offset Cutting Blades (in)	6.0 height x 3/8 thick; (2) Reversible and Replaceable		
Skid Shoes (in)	Replaceable, 2.0 wide x 1/4 thick		
Warranty	Residential, semi-commercial, regular commercial use: 1 year		
SKU No.	KLL60	KLL72	KLL84
TRACTOR COMPATIBILITY	5 FT	6 FT	7 FT
eMax 25L	X	X	X
Max 25XL	X	X	X
Max 26XLT	X	X	X
1626	X	X	X
1635	X	X	X
1640		X	X
2638	X	X	X
2645	X	X	X
2660		X	X
2670			X
3640		X	X
3650		X	X
4540 2WD / 4WD	X	X	X
4550 4WD		X	X



AUGERS

PTO-POWERED EARTH-DRILLING TOOL

Drop the shovels, post hole diggers, and digging bars. Mahindra earth augers are well-suited for home gardeners, farmers, ranchers, landscapers, nurseries, and residential and commercial construction. They work with subcompact, compact, and utility tractors that displace 25 - 65 PTO hp. These beasts bore through compacted and rocky ground — nearly 4 ft deep — using their heavy-duty high-carbon steel cutting edges, protected by a heavy-duty gearbox and shear bolt. Combined with your tractor's PTO power, our augers make fence building and tree planting a lot quicker and easier.

FEATURES & BENEFITS

- CAT 1 or 2 compatible
- Shear-bolt protection for your valuable investment
- 6, 9 and 12-inch hole widths and 45-inch boring depth
- Rugged gearbox with robust 2-inch diameter output shaft
- Replaceable, high-carbon steel cutting edges



SPECIFICATIONS

AUGER FEATURES	BORING BITS			DRIVE UNIT
Boring Diameter (in)	6	9	12	—
Maximum Auger Diameter (in)	—			12 ^[9]
Boring Depth (in)	45			—
Digger Weight (lb)	180			210
Auger Weight (lb)	30	41	60	-
Tractor PTO (hp)	25 – 65			
Hitch Category	1 or 2			
Gear Box Output Shaft Dia. (in)	2			2.92
Cutting edges	Replaceable, high-carbon steel			—
Gear-Box Protection	Shear Bolt			
Warranty	Residential, semi-commercial, regular commercial use: 1 year			
SKU No.	KPHD6A0	KPHD9A0	KPHD12A0	KPHDNOAUG
AUGER FEATURES	BORING BITS			DRIVE UNIT
eMax 25L	X			
Max 25XL	X			
Max 26XLT	X	X		
1626	X	X	X	X
1635	X	X	X	X
1640	X	X	X	X
2638	X	X	X	X
2645		X	X	X
2660			X	X
2670				X
3640				X
3650				X
4540 2WD / 4WD				X
4550 4WD				X
6065 / 6075				X
7085 / 7095				X
8090 / 8100				X

[9] Auger not included



COMPACTORS

PACK DOWN GRANULAR SOIL AND GRAVEL

Mahindra soil compactors can be useful tools for home gardeners, farmers, ranchers, landscapers, nurseries, parks and recreation, and residential contractors. Compacting and smoothing out soil helps resist water infiltration, erosion, and being carried away by the wind. Our pull-type compactors are with subcompact, compact, and utility tractors. They're workhorses, built with a heavy steel frame and roller.

FEATURES & BENEFITS

- Available in 4- and 6-ft widths
- Heavy steel roller for consistent and smooth soil compaction
- 12-inch hollow roller equipped with 1-inch plug inlet to add sand or water when extra weight is needed
- Two support stands included
- One-year warranty for peace of mind

SPECIFICATIONS

COMPACTOR FEATURES	4 FT	6 FT
Size (in)	48	72
Type	3-pt Lift	3-pt Lift
Smooth Steel Roller (in)	12	
Empty Weight (lb)	302	394
Filled Weight (lb)	512	710
Support Stands	2	
Warranty	Residential, semi-commercial, regular commercial use: 1 year	
SKU No.	KCP3PT412	KCP3PT612
TRACTOR COMPATIBILITY	4 FT	6 FT
eMax 25L	X	
Max 25XL	X	
Max 26XLT	X	
1626		X
1635		X
1640		X
2638		X
2645		X
2660		X
2670		X
3640		X
3650		X
4540 2WD / 4WD		X
4550 4WD		X



SPREADERS

BROADCAST FERTILIZER AND SEED

Mahindra spreaders evenly distribute fertilizer, grass seed & small grain seed. There are two size configurations to operate with your CAT 1 subcompact, compact, or utility tractor. The pull-type model tows with a tractor, ATV, or UTV. Unlike some hoppers, ours are made from thick poly to prevent corrosion. The 440-lb models can carry almost nine 50-lb bags of fertilizer while the 990-lb version holds 18.

FEATURES & BENEFITS

- Two CAT 1 and one pull-type configurations
- Heavy-duty poly hopper to prevent corrosion
- 440- and 990-lb load capacities
- One-year warranty for peace of mind

SPECIFICATIONS

SPREADER FEATURES	480 LB LIFT	1020 LB LIFT	480 LB PULL
Approximate Weight (lb)	119	139	185
Hopper Type	Poly		
Hopper Capacity (lb)	440	990	440
Height (in)	36	44.5	—
Spreading Width (ft)	20 - 46		—
Spreader Drive	PTO		Ground Driven
Gearbox	1 to 1		—
Gearbox Disengagement	—		Pin
Spreader Pattern	—		Rear, Left, Right
Spreader Rate Adjustment	—		Lever Type
PTO Diameter (in)	1-3/8		—
Hitch Ball Diameter (in)	—	—	1-7/8
Hitch Type	CAT 1		Adjustable Tongue
Wheels (in)	—	—	(2) Pneumatic 16x6.5 Turf Tread
Frame	Tubular Steel		
Hopper Agitator	Yes		
Warranty	Residential, semi-commercial, regular commercial use: 1 year		
SKU No.	KFS3PT480	KFS3PT120	KFSDW480
TRACTOR COMPATIBILITY	480 LB LIFT	1020 LB LIFT	480 LB PULL
Max 25XL	X		X
Max 26XLT	X		X
1626	X	X	X
1635	X	X	X
1640	X	X	X
2638	X	X	X
2645	X	X	X
2660	X	X	X
2670	X	X	
3640	X	X	X
3650	X	X	X
4540 2WD / 4WD	X	X	X
4550 4WD	X	X	X



PLOW

A FURROWING, TRENCHING, AND UNEARTHING TOOL

Save your energy using our versatile plow, an inexpensive implement that saves you time furrowing a row garden, trenching a ditch to improve drainage, and unearthing root vegetables like potatoes and turnips. And, it's get-it-done frame and blade digs to depths of 12-inches.

FEATURES & BENEFITS

- Works with subcompact and compact tractors rated up to 40 horsepower
- 12-inch digging depth capacity
- 3-pt, CAT 1 compatible
- One-year warranty for peace of mind

SPECIFICATIONS

FEATURES	PLOW
Max Engine Rating (hp)	40
Hitch Category	1
Dig Depth (in)	12
Warranty	Residential, semi-commercial, regular commercial use: 1 year
SKU No.	KPP
TRACTOR COMPATIBILITY	PLOW
eMax 25L	X
Max 25XL	X
Max 26XLT	X
1626	X
1635	X



HITCHES

3-PT QUICK HITCH AND TRAILER MOVER

Mahindra 3-pt quick hitch is a back and time-saver, eliminating the need to remove or replace connector pins.^[10] Instead, quick-release levers lock around your tractor's pre-installed hooks in only a few seconds.

The Mahindra trailer mover is a must-have 3-pt hitch to help you move equipment, including boats, machinery, and trailers around your property.^[11]

3-PT QUICK HITCH FEATURES & BENEFITS

- 3-pt, CAT 1 or 2 compatible
- Heavy-duty construction
- Auto-locking levers save valuable time attaching and quick-releasing implements
- Available for subcompact, compact, and utility tractors rated up to 140 horsepower

TRAILER MOVER FEATURES & BENEFITS

- 3-pt, CAT 1 quick-hitch compatible
- Moves bumper-pull and gooseneck trailers
- One-year warranty for peace of mind

SPECIFICATIONS

HITCH FEATURES	CAT 1 QUICK HITCH	CAT 2 QUICK HITCH	TRAILER MOVER
Max Engine Rating (hp)	70	125	60
Hitch Category	1	2	1
Quick-hitch Compatible	—		Yes
Weight (lb)	84		—
Top Hook	Adjustable		—
Hitch Auto-lock	Yes		—
Construction	Heavy-duty		—
Quick-release Function	Levers		—
Overall Depth (in)	—		37.5
Overall Height (in)	—		20.5
Overall Width (in)	—		25
Max Spear Length (in)	—		40
Max Spear Lift Capacity (lb)	—		2000
Warranty	Residential, semi-commercial, regular commercial use: 1 year		
SKU No.	KQHCATI	KQHCATII	KTM0V3PT
TRACTOR COMPATIBILITY	CAT 1 QUICK HITCH	CAT 2 QUICK HITCH	TRAILER MOVER
eMax 20S/22L	X		
eMax 25L	X		
Max 25XL	X		X
Max 26XLT	X		X
1626	X		X
1635	X		X
1640	X		X
2638	X		X
2645	X		X
2660	X		X
2670	X	X	
3640	X	X	X
3650	X	X	X
4540 2WD / 4WD	X	X	X
4550 4WD	X	X	X
6065 / 6075		X	
7085 / 7095		X	
8090 / 8100		X	
9110 / 9125		X	

[10] PTO is a separate connection [11] Ball mounts and balls shown for display purposes only, and are sold separately



BOOM POLE

LIFT HEAVY, DIFFICULT-TO-MOVE MATERIALS

The Mahindra boom pole is a handy lifting tool when hitched to a CAT 1 utility tractor. The heavy-duty tubular frame is capable of handling up to 1,800 lb. The boom pole is ideal for lifting engine blocks, logs, posts, and other heavy materials.

FEATURES & BENEFITS

- Compatible with utility tractors rated up to 60 horsepower
- 3-pt, CAT 1 quick-hitch compatible
- 1,800-lb lifting capacity
- One-year warranty for peace of mind

SPECIFICATIONS

FEATURES	BOOM POLE
Max Engine Rating (hp)	60
Hitch Category	1
Quick-hitch Compatible	Yes
Length (in)	83
Frame (in)	2.5 steel tubes with 3/16 L-shaped truss supports
Lifting Capacity (lb)	1,800
Warranty	Residential, semi-commercial, regular commercial use: 1 year
SKU No.	KBPH
TRACTOR COMPATIBILITY	BOOM POLE
3640	X
3650	X
4540 2WD / 4WD	X
4550 4WD	X

Mahindra



**OFFICIAL
TRACTOR
OF TOUGH™**

Mahindra USA, Inc.

9020 Jackrabbit Road, Suite 600

Houston, Texas 77095

877-449-7771

mahindrausa.com

mahinracanada.com

Mahindra USA, Inc., reserves the right to change the stated specifications without notice. This brochure is for descriptive purposes only and reasonable efforts were made to verify the information contained in it. Some items shown may be optional and some machinery shown may not be available at all dealers. Mahindra disclaims all representations and warranties, express or implied, or any liability from the use of this brochure. For complete warranty, safety, and product information, consult your local Mahindra dealer and the product operation manual. Engine power (hp/kw) and other specifications are based on various standards and best practices. This brochure is intended for the United States and its territories only. For more information visit our website.

MAH10132020